

> THE BEST MACHINE FOR YOU

Overview of machines

| Sheet thickness in mm ↓ | | Capacity in width in mm | | | | | |
|---|----|-------------------------|------|------|------|------|------|
| | | 500 | 1000 | 1500 | 2000 | 2500 | 3000 |
| Bending machine in standard configuration | 2 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 3 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 4 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 5 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 6 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 8 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 10 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 12 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 15 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 16 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 18 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 20 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 25 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Hydraulic dynamic camber (patented) | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Manually adjustable back gauge | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Motorized back gauge | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Electronic adjustment of the bending beam | | | | | | | |
| → with legible selection switch | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| → with automatic sheet thickness detection | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Touchscreen | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Graphic touchscreen | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Goat foot segments with collecting rail | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Automatic clamping of the goat foot | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Stepless pressure regulation of upper beam | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Round bending function with initial round bending | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Function extension "cone bending" | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Segmented bending beam rail | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Increased speed of bending beam | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Increased lift of upper beam up to 1000 mm | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Swiveling upper beam | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Extension of bending beam up to 150° | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

Materials: Mild steel, Stainless steel, copper, lexan, molybdenum, magnesium, aluminium, plastics

